

Dodge

SAFETY DATA SHEET

Dis-Spray

According to Regulation (EC) No 1907/2006, Annex II, as amended. Commission Regulation (EU) No 2015/830 of 28 May 2015.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name Dis-Spray

Product number 505030

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Embalming Spray

1.3. Details of the supplier of the safety data sheet

Supplier Dodge Company Ltd.
Units 11/15 Ardglen Industrial Estate,
Whitchurch, Hampshire,
RG28 7BB, United Kingdom
+44 (0)1256-893883
+44 (0)1256-893868
enquiries@dodge-uk.com

1.4. Emergency telephone number

Emergency telephone +44 (0)1256 893883 (Mon- Fri 9:00 am - 4:30 pm)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Flam. Liq. 2 - H225

Health hazards Eye Irrit. 2 - H319 STOT SE 3 - H336

Environmental hazards Aquatic Chronic 2 - H411

2.2. Label elements

Hazard pictograms



Signal word

Danger

Hazard statements

EUH208 Contains 3-Iodo-2-propynyl butylcarbamate. May produce an allergic reaction.
H225 Highly flammable liquid and vapour.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.

Dis-Spray

Precautionary statements	<p>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</p> <p>P261 Avoid breathing vapour/ spray.</p> <p>P273 Avoid release to the environment.</p> <p>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.</p> <p>P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.</p> <p>P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.</p> <p>P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>P312 Call a POISON CENTRE/doctor if you feel unwell.</p> <p>P501 Dispose of contents/ container in accordance with national regulations.</p>
Contains	Propan-2-ol
Supplementary precautionary statements	<p>P240 Ground and bond container and receiving equipment.</p> <p>P241 Use explosion-proof electrical equipment.</p> <p>P242 Use non-sparking tools.</p> <p>P243 Take action to prevent static discharges.</p> <p>P264 Wash contaminated skin thoroughly after handling.</p> <p>P271 Use only outdoors or in a well-ventilated area.</p> <p>P337+P313 If eye irritation persists: Get medical advice/ attention.</p> <p>P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.</p> <p>P391 Collect spillage.</p> <p>P403+P233 Store in a well-ventilated place. Keep container tightly closed.</p> <p>P403+P235 Store in a well-ventilated place. Keep cool.</p> <p>P405 Store locked up.</p>

2.3. Other hazards

This substance is not classified as PBT or vPvB according to current EU criteria.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Propan-2-ol		50 - 100%
CAS number: 67-63-0	EC number: 200-661-7	REACH registration number: 01-2119457558-25-XXXX
Classification		
Flam. Liq. 2 - H225		
Eye Irrit. 2 - H319		
STOT SE 3 - H336		
Ethanediol		0.5 - <1%
CAS number: 107-21-1	EC number: 203-473-3	
Classification		
Acute Tox. 4 - H302		
STOT RE 2 - H373		

Dis-Spray

Quaternary ammonium compounds, C12-14-alkyl[(ethylphenyl)methyl]dimethyl, chlorides	0.25 - <0.5%
CAS number: 85409-23-0 EC number: 287-090-7 M factor (Acute) = 10	
Classification Acute Tox. 4 - H302 Acute Tox. 4 - H312 Skin Corr. 1B - H314 Aquatic Acute 1 - H400	
Quaternary ammonium compounds, benzyl-C12-18-alkyldimethyl, chlorides	0.25 - <0.5%
CAS number: 68391-01-5 EC number: 269-919-4 M factor (Acute) = 1	
Classification Acute Tox. 4 - H302 Acute Tox. 4 - H312 Skin Corr. 1B - H314 Eye Dam. 1 - H318 Aquatic Acute 1 - H400	
3-Iodo-2-propynyl butylcarbamate	0.025 - <0.25%
CAS number: 55406-53-6 EC number: 259-627-5 M factor (Acute) = 10 M factor (Chronic) = 1	
Classification Acute Tox. 4 - H302 Acute Tox. 3 - H331 Eye Dam. 1 - H318 Skin Sens. 1 - H317 STOT RE 1 - H372 Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410	
Triclosan	0.025 - <0.25%
CAS number: 3380-34-5 EC number: 222-182-2 M factor (Acute) = 100 M factor (Chronic) = 100	
Classification Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410	

Dis-Spray

Ethanol	0.025 - <0.25%
CAS number: 64-17-5	EC number: 200-578-6
Classification	
Flam. Liq. 2 - H225	
Eye Irrit. 2 - H319	
Amines, C12-18-alkyldimethyl	<0.025%
CAS number: 68391-04-8	EC number: 269-923-6
M factor (Acute) = 100	M factor (Chronic) = 1
Classification	
Acute Tox. 4 - H302	
Skin Corr. 1B - H314	
Eye Dam. 1 - H318	
Aquatic Acute 1 - H400	
Aquatic Chronic 1 - H410	

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	If in doubt, get medical attention promptly.
Inhalation	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention if any discomfort continues.
Ingestion	Rinse mouth thoroughly with water. Give a few small glasses of water or milk to drink. Get medical attention if any discomfort continues.
Skin contact	Wash skin thoroughly with soap and water. Wash contaminated clothing before reuse. Get medical attention if irritation persists after washing.
Eye contact	Remove any contact lenses and open eyelids wide apart. Rinse with water. Continue to rinse for at least 10 minutes. Get medical attention promptly if symptoms occur after washing.

4.2. Most important symptoms and effects, both acute and delayed

General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	Vapours may cause headache, fatigue, dizziness and nausea.
Ingestion	Dryness of mouth and throat. May cause discomfort if swallowed.
Skin contact	Dryness and/or cracking. May cause skin sensitisation or allergic reactions in sensitive individuals.
Eye contact	Irritating to eyes.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	Treat symptomatically.
-----------------------------	------------------------

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog.
-------------------------------------	--

Dis-Spray

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Hazardous combustion products Carbon dioxide (CO₂). Carbon monoxide (CO).

5.3. Advice for firefighters

Protective actions during firefighting Avoid breathing fire gases or vapours. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. Control run-off water by containing and keeping it out of sewers and watercourses.

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid inhalation of vapours. Avoid contact with eyes. Wear protective clothing as described in Section 8 of this safety data sheet.

6.2. Environmental precautions

Environmental precautions Do not discharge into drains or watercourses or onto the ground.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Eliminate all sources of ignition. Provide adequate ventilation. Wear protective clothing as described in Section 8 of this safety data sheet. Absorb spillage with non-combustible, absorbent material. Place waste in labelled, sealed containers. Dispose of contents/container in accordance with national regulations.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. See Section 11 for additional information on health hazards. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Read and follow manufacturer's recommendations. Avoid inhalation of vapours and contact with skin and eyes.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly-closed, original container in a dry, cool and well-ventilated place.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

Propan-2-ol

Long-term exposure limit (8-hour TWA): WEL 400 ppm 999 mg/m³

Short-term exposure limit (15-minute): WEL 500 ppm 1250 mg/m³

Ethanediol

Dis-Spray

Long-term exposure limit (8-hour TWA): WEL 20 ppm 52 mg/m³ vapour

Short-term exposure limit (15-minute): WEL 40 ppm 104 mg/m³ vapour

Sk

Long-term exposure limit (8-hour TWA): WEL 10 mg/m³ particulate

Sk

Ethanol

Long-term exposure limit (8-hour TWA): WEL 1000 ppm 1920 mg/m³

WEL = Workplace Exposure Limit

Sk = Can be absorbed through the skin.

8.2. Exposure controls

Appropriate engineering controls	Observe any occupational exposure limits for the product or ingredients. This product is not to be used under conditions of poor ventilation.
Eye/face protection	The following protection should be worn: Tight-fitting safety glasses. Personal protective equipment for eye and face protection should comply with European Standard EN166.
Hand protection	Wear protective gloves. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. To protect hands from chemicals, gloves should comply with European Standard EN374.
Other skin and body protection	Wear suitable protective clothing as protection against splashing or contamination.
Hygiene measures	Do not eat, drink or smoke when using this product. Provide eyewash station. Wash hands thoroughly after handling. Wash contaminated clothing before reuse. Wash at the end of each work shift and before eating, smoking and using the toilet.
Respiratory protection	Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit. Ensure all respiratory protective equipment is suitable for its intended use and is 'CE'-marked.
Environmental exposure controls	Keep container tightly sealed when not in use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Clear liquid.
Colour	Blue.
Odour	Mild. Alcoholic.
Odour threshold	Not available.
pH	Not available.
Melting point	Not available.
Initial boiling point and range	75-77°C @ 760 mm Hg
Flash point	12°C Closed cup.
Evaporation rate	> 1 (butyl acetate = 1)
Flammability (solid, gas)	Flammable liquid and vapour.
Upper/lower flammability or explosive limits	Lower flammable/explosive limit: 2% Upper flammable/explosive limit: 12%

Dis-Spray

Vapour pressure	33 mm Hg @ 20°C
Vapour density	> 1
Relative density	0.86-0.88 @ 20°C
Solubility(ies)	Soluble in water.
Partition coefficient	Not available.
Auto-ignition temperature	Not available.
Decomposition Temperature	Not available.
Viscosity	Not available.
Explosive properties	Not considered to be explosive.
Oxidising properties	Does not meet the criteria for classification as oxidising.

9.2. Other information

Volatility	99.6%
------------	-------

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	See the other subsections of this section for further details.
------------	--

10.2. Chemical stability

Stability	Stable at normal ambient temperatures and when used as recommended.
-----------	---

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	In use may form flammable/explosive vapour-air mixture. Reactions with the following materials may generate heat: Oxidising agents.
------------------------------------	---

10.4. Conditions to avoid

Conditions to avoid	Keep away from heat, sparks and open flame.
---------------------	---

10.5. Incompatible materials

Materials to avoid	Oxidising agents.
--------------------	-------------------

10.6. Hazardous decomposition products

Hazardous decomposition products	Does not decompose when used and stored as recommended.
----------------------------------	---

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

Notes (oral LD ₅₀)	Based on available data the classification criteria are not met.
--------------------------------	--

Acute toxicity - dermal

Notes (dermal LD ₅₀)	Based on available data the classification criteria are not met.
----------------------------------	--

Acute toxicity - inhalation

Notes (inhalation LC ₅₀)	Based on available data the classification criteria are not met.
--------------------------------------	--

ATE inhalation (dusts/mists mg/l)	358.29
-----------------------------------	--------

Skin corrosion/irritation

Dis-Spray

Animal data	Based on available data the classification criteria are not met.
<u>Serious eye damage/irritation</u>	
Serious eye damage/irritation	Causes serious eye irritation.
<u>Respiratory sensitisation</u>	
Respiratory sensitisation	Based on available data the classification criteria are not met.
<u>Skin sensitisation</u>	
Skin sensitisation	May cause skin sensitisation or allergic reactions in sensitive individuals.
<u>Germ cell mutagenicity</u>	
Genotoxicity - in vitro	Based on available data the classification criteria are not met.
<u>Carcinogenicity</u>	
Carcinogenicity	Based on available data the classification criteria are not met.
<u>Reproductive toxicity</u>	
Reproductive toxicity - fertility	Based on available data the classification criteria are not met.
Reproductive toxicity - development	Based on available data the classification criteria are not met.
<u>Specific target organ toxicity - single exposure</u>	
STOT - single exposure	STOT SE 3 - H336 May cause drowsiness or dizziness.
<u>Specific target organ toxicity - repeated exposure</u>	
STOT - repeated exposure	Based on available data the classification criteria are not met.
<u>Aspiration hazard</u>	
Aspiration hazard	Based on available data the classification criteria are not met.
Inhalation	Vapours may cause headache, fatigue, dizziness and nausea.
Ingestion	Dryness of mouth and throat. May cause discomfort if swallowed.
Skin contact	Dryness and/or cracking. May cause skin sensitisation or allergic reactions in sensitive individuals.
Eye contact	Irritating to eyes.
Medical considerations	Allergies.

Toxicological information on ingredients.

Propan-2-ol

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 5,840.0

Species Rat

Notes (oral LD₅₀) REACH dossier information.

ATE oral (mg/kg) 5,840.0

Skin corrosion/irritation

Animal data Primary dermal irritation index: 0 REACH dossier information.

Serious eye damage/irritation

Dis-Spray

Serious eye damage/irritation	Dose: 0.1 ml, 1 second, Rabbit REACH dossier information. Irritating.
<u>Skin sensitisation</u>	
Skin sensitisation	Buehler test - Guinea pig: Not sensitising. REACH dossier information.
<u>Germ cell mutagenicity</u>	
Genotoxicity - in vitro	Gene mutation: Negative. REACH dossier information.
Genotoxicity - in vivo	Chromosome aberration: Negative. REACH dossier information.
<u>Carcinogenicity</u>	
Carcinogenicity	NOEL 5000 ppm, Inhalation, Rat REACH dossier information.
IARC carcinogenicity	IARC Group 3 Not classifiable as to its carcinogenicity to humans.
<u>Specific target organ toxicity - single exposure</u>	
STOT - single exposure	STOT SE 3 - H336 May cause drowsiness or dizziness.
Target organs	Central nervous system
<u>Specific target organ toxicity - repeated exposure</u>	
STOT - repeated exposure	NOAEC 5000 ppm, Inhalation, Rat REACH dossier information.

Triclosan

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg)	5,001.0
Species	Rat
Notes (oral LD₅₀)	REACH dossier information. Based on available data the classification criteria are not met.
ATE oral (mg/kg)	5,001.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg)	6,001.0
Species	Rabbit
Notes (dermal LD₅₀)	REACH dossier information. Based on available data the classification criteria are not met.
ATE dermal (mg/kg)	6,001.0

Acute toxicity - inhalation

Notes (inhalation LC₅₀)	Based on available data the classification criteria are not met.
---	--

Skin corrosion/irritation

Animal data	Dose: 0.5 mL, 24 hours, Rabbit Erythema/eschar score: Well defined erythema (2). Oedema score: Very slight oedema - barely perceptible (1). REACH dossier information. Irritating.
--------------------	--

Serious eye damage/irritation

Dis-Spray

Serious eye damage/irritation	Causes serious eye irritation.
<u>Respiratory sensitisation</u>	
Respiratory sensitisation	Based on available data the classification criteria are not met.
<u>Skin sensitisation</u>	
Skin sensitisation	Buehler test - Guinea pig: Not sensitising. REACH dossier information. Based on available data the classification criteria are not met.
<u>Germ cell mutagenicity</u>	
Genotoxicity - in vitro	Gene mutation: Negative. REACH dossier information. Based on available data the classification criteria are not met.
Genotoxicity - in vivo	Chromosome aberration: Negative. REACH dossier information. Based on available data the classification criteria are not met.
<u>Carcinogenicity</u>	
Carcinogenicity	NOAEL 3000 ppm, Oral, Rat REACH dossier information. Based on available data the classification criteria are not met.
<u>Reproductive toxicity</u>	
Reproductive toxicity - fertility	Two-generation study - NOAEL 3000 ppm, Oral, Rat P REACH dossier information. Based on available data the classification criteria are not met.
Reproductive toxicity - development	Developmental toxicity: - NOAEL: 150 mg/kg/day, Oral, Rabbit REACH dossier information. Based on available data the classification criteria are not met.
<u>Specific target organ toxicity - single exposure</u>	
STOT - single exposure	Based on available data the classification criteria are not met.
<u>Specific target organ toxicity - repeated exposure</u>	
STOT - repeated exposure	NOAEL 50 ppm, Oral, Mouse REACH dossier information. Based on available data the classification criteria are not met.
<u>Aspiration hazard</u>	
Aspiration hazard	Based on available data the classification criteria are not met.

SECTION 12: Ecological information

12.1. Toxicity

Toxicity Toxic to aquatic life with long lasting effects.

Ecological information on ingredients.

Propan-2-ol

Toxicity	No negative effects on the aquatic environment are known.
<u>Acute aquatic toxicity</u>	
Acute toxicity - fish	LC ₅₀ , 96 hours: 10000 mg/l, Pimephales promelas (Fat-head Minnow) REACH dossier information.
Acute toxicity - aquatic invertebrates	LC ₅₀ , 24 hours: > 10000 mg/l, Daphnia magna REACH dossier information.

Dis-Spray

Acute toxicity - aquatic plants Toxicity threshold, 7 days: 1800 mg/l, Scenedesmus quadricauda REACH dossier information.

Triclosan

Toxicity Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410 Very toxic to aquatic life with long lasting effects.

Acute aquatic toxicity

M factor (Acute) 100

Acute toxicity - fish LC₅₀, 96 hours: 0.54 mg/l, Brachydanio rerio (Zebra Fish)

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: >0.18 mg/l, Daphnia magna

Acute toxicity - aquatic plants EC₅₀, 72 hours: 0.001 mg/l, Desmodesmus subspicatus

Chronic aquatic toxicity

NOEC 0.0001 < NOEC ≤ 0.001

Degradability Non-rapidly degradable

M factor (Chronic) 100

12.2. Persistence and degradability

Persistence and degradability The degradability of the product is not known.

Ecological information on ingredients.

Propan-2-ol

Persistence and degradability The product is readily biodegradable.

Biodegradation Water - Degradation (53%): 5 days
REACH dossier information.
The substance is readily biodegradable.

Biological oxygen demand 1.19 - 1.72 g O₂/g substance REACH dossier information.

Chemical oxygen demand 2.23 g O₂/g substance REACH dossier information.

Triclosan

Persistence and degradability The product is not readily biodegradable.

Phototransformation Water - DT₅₀ : 23.9 hours
Estimated value.

Biodegradation Water - Degradation 37%: 28 days

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient Not available.

Ecological information on ingredients.

Dis-Spray

Propan-2-ol

Bioaccumulative potential No data available on bioaccumulation.

Triclosan

Bioaccumulative potential BCF: 2532, Brachydanio rerio (Zebra Fish)

Partition coefficient log Pow: 4.8

12.4. Mobility in soil

Mobility Mobile.

Ecological information on ingredients.

Propan-2-ol

Mobility Soluble in water.

Triclosan

Mobility The product is partly soluble in water and may spread in the aquatic environment.

Adsorption/desorption coefficient Water - log Koc: 2.92 @ 20°C

Henry's law constant 0.000506 Pa m³/mol @ 25°C Estimated value.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

Ecological information on ingredients.

Propan-2-ol

Results of PBT and vPvB assessment This substance is not classified as PBT or vPvB according to current EU criteria.

Triclosan

Results of PBT and vPvB assessment This substance is not classified as PBT or vPvB according to current EU criteria.

12.6. Other adverse effects

Other adverse effects None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal methods The packaging must be empty (drop-free when inverted). Dispose of contents/container in accordance with national regulations.

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID) 1993

UN No. (IMDG) 1993

Dis-Spray

UN No. (ICAO) 1993

UN No. (ADN) 1993

14.2. UN proper shipping name

Proper shipping name (ADR/RID) FLAMMABLE LIQUID, N.O.S. (CONTAINS Propan-2-ol, Triclosan)

Proper shipping name (IMDG) FLAMMABLE LIQUID, N.O.S. (CONTAINS Propan-2-ol, Triclosan, Quaternary ammonium compounds, C12-14-alkyl[(ethylphenyl)methyl]dimethyl, chlorides, 3-Iodo-2-propynyl butylcarbamate)

Proper shipping name (ICAO) FLAMMABLE LIQUID, N.O.S. (CONTAINS Propan-2-ol, Triclosan)

Proper shipping name (ADN) FLAMMABLE LIQUID, N.O.S. (CONTAINS Propan-2-ol, Triclosan)

14.3. Transport hazard class(es)

ADR/RID class 3

ADR/RID classification code F1

ADR/RID label 3

IMDG class 3

ICAO class/division 3

ADN class 3

Transport labels



14.4. Packing group

ADR/RID packing group II

IMDG packing group II

ICAO packing group II

ADN packing group II

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



14.6. Special precautions for user

EmS F-E, S-E

ADR transport category 2

Emergency Action Code •3YE

Hazard Identification Number (ADR/RID) 33

Tunnel restriction code (D/E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Dis-Spray

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations	The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations 2009 (SI 2009 No. 1348) (as amended) ["CDG 2009"]. EH40/2005 Workplace exposure limits.
EU legislation	Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended). Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended). Commission Regulation (EU) No 2015/830 of 28 May 2015.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Classification abbreviations and acronyms	Acute Tox. = Acute toxicity Aquatic Acute = Hazardous to the aquatic environment (acute) Aquatic Chronic = Hazardous to the aquatic environment (chronic) Eye Dam. = Serious eye damage Eye Irrit. = Eye irritation Flam. Liq. = Flammable liquid Skin Corr. = Skin corrosion Skin Irrit. = Skin irritation STOT SE = Specific target organ toxicity-single exposure
Training advice	Only trained personnel should use this material.
Revision comments	Revised regulations.
Revision date	21/08/2019
Revision	10
Supersedes date	27/11/2018
SDS number	595

Dis-Spray

Hazard statements in full

H225 Highly flammable liquid and vapour.
H302 Harmful if swallowed.
H312 Harmful in contact with skin.
H314 Causes severe skin burns and eye damage.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H331 Toxic if inhaled.
H336 May cause drowsiness or dizziness.
H372 Causes damage to organs (Larynx) through prolonged or repeated exposure.
H373 May cause damage to organs (Kidneys) through prolonged or repeated exposure if swallowed.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
H411 Toxic to aquatic life with long lasting effects.
EUH208 Contains 3-Iodo-2-propynyl butylcarbamate. May produce an allergic reaction.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.